

High-Quality Cylindrical Aluminum Nitride Ceramic Crucibles



Size details:

Item NO.	Outer Diameter/mm	Height/mm	Thickness/mm	coefficient of thermal conductivity
CX-AIN-12002	5	5	3	≥170W/m.k
CX-AIN-12003	16	56	3	≥170W/m.k
CX-AIN-12004	17	40	3	≥170W/m.k
CX-AIN-12005	19	35	3	≥170W/m.k
CX-AIN-12006	19	58	3	≥170W/m.k
CX-AIN-12007	20	30	3	≥170W/m.k
CX-AIN-12008	20	40	3	≥170W/m.k
CX-AIN-12009	20	50	3.5	≥170W/m.k
CX-AIN-12010	22	36	3.5	≥170W/m.k
CX-AIN-12011	22	25	3.5	≥170W/m.k
CX-AIN-12012	23	60	3.5	≥170W/m.k
CX-AIN-12013	25	25	4	≥170W/m.k
CX-AIN-12014	25	30	4	≥170W/m.k
CX-AIN-12015	25	60	4	≥170W/m.k
CX-AIN-12016	30	28	4	≥170W/m.k
CX-AIN-12017	30	30	4	≥170W/m.k
CX-AIN-12018	35	30	4	≥170W/m.k
CX-AIN-12019	47	13	4	≥170W/m.k
CX-AIN-12020	60	105	5	≥170W/m.k
CX-AIN-12021	88	150	5	≥170W/m.k
CX-AIN-12022	100	100	6	≥170W/m.k
CX-AIN-12023	110	110	6	≥170W/m.k
CX-AIN-12024	110	150	6	≥170W/m.k
CX-AIN-12025	115	110	6	≥170W/m.k
CX-AIN-12026	115	155	6	≥170W/m.k
CX-AIN-12027	120	120	7	≥170W/m.k
CX-AIN-12028	125	150	7	≥170W/m.k
CX-AIN-12029	130	130	7	≥170W/m.k
CX-AIN-12030	135	30	7	≥170W/m.k
CX-AIN-12031	135	110	7	≥170W/m.k
CX-AIN-12032	140	140	8	≥170W/m.k

Note: We can customize aluminum nitride crucibles dimensions upon request.

The listed dimensions are for reference only. Please contact us if you require tight tolerances.

Judy Li (Judy@ceramxpert.com)

Mobile / WhatsApp / WeChat: 0086-19373310917

Website: www.ceramxpert.com